

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY) 2. REPORT TYPE Technical Papers 3. DATES COVERED (From - To)

4. TITLE AND SUBTITLE 5a. CONTRACT NUMBER

5b. GRANT NUMBER

5c. PROGRAM ELEMENT NUMBER

6. AUTHOR(S) 5d. PROJECT NUMBER

5e. TASK NUMBER

5f. WORK UNIT NUMBER

8. PERFORMING ORGANIZATION REPORT

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Air Force Research Laboratory (AFMC)
AFRL/PRS
5 Pollux Drive
Edwards AFB CA 93524-7048

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Air Force Research Laboratory (AFMC)
AFRL/PRS
5 Pollux Drive
Edwards AFB CA 93524-7048

10. SPONSOR/MONITOR'S ACRONYM(S)

11. SPONSOR/MONITOR'S NUMBER(S)

12. DISTRIBUTION / AVAILABILITY STATEMENT

Approved for public release; distribution unlimited.

13. SUPPLEMENTARY NOTES

14. ABSTRACT

20030128 230

15. SUBJECT TERMS

16. SECURITY CLASSIFICATION OF:

a. REPORT b. ABSTRACT c. THIS PAGE

Unclassified Unclassified Unclassified

17. LIMITATION OF ABSTRACT

A

18. NUMBER OF PAGES

19a. NAME OF RESPONSIBLE PERSON

Leilani Richardson

19b. TELEPHONE NUMBER

(include area code)
(661) 275-5015

MEMORANDUM FOR PRS (In-House Publication)

62

FROM: PROI (STINFO)

22 Jan 2001

SUBJECT: Authorization for Release of Technical Information, Control Number: **AFRL-PR-ED-AB-2001-021**
Liu, C.T., "Investigating Cumulative Damage in a Highly Filled Polymeric Material"

Abstract for 2001 Joint Applied Mechanics and Materials Summer Conf.
(San Diego, CA June 27-29, 2001) (Deadline: 05 Feb 01)

(Statement A)

Investigating Cumulative Damage in a Highly Filled Polymeric Material

C.T. Liu

AFRL/PRSM

10 East Saturn Boulevard
Edwards AFB CA 93524-7680

A highly filled polymeric material, which consists of a large number of fine particles, on the microscopic scale, can be considered nonhomogeneous. When this material is stretched, the different sizes and distribution of the filler particles, the different crosslinking density of the polymer chains, and the variation of the bond strength between the particles and the binder can produce highly nonhomogeneous local stress and strength fields. Because of the particle's high rigidity relative to the binder, the local stress is significantly higher than the applied stress, especially when the particles are close to each other. Since local stress and strength vary in a random fashion, the failure site in the material also varies randomly and does not necessarily coincide with the maximum stress location. In other words, the location and degree of damage will also vary randomly in the material. The damage may appear in the form of microcracks and microvoids in the binder, or in the form of particle/binder separation known as dewetting. When the particle is dewetted, the local stress will be redistributed. With time, additional particle/binder separation and vacuole formation takes place. This time-dependent process of dewetting nucleation, or damage nucleation, is due to the time-dependent processes of stress redistribution and particle/binder separation. Depending on the formation of the material and the testing condition, damage growth may take place as material tearing or by successive nucleation and coalescence of the microvoids. These damage initiation and evolution processes are time-dependent, and are the main factors responsible for the time-sensitivity of the strength degradation as well as the fracture behavior of the material.

In this study, a damage parameter, based on a linear cumulative theory, was used to determine the damage state in the material under constant strain rate and dual-strain rate loading conditions. During the tests, volume dilatations were measured. The relationships among the damage parameter, volume dilatation, and the constitutive behavior of the material were investigated. In addition, ultrasonic techniques were used to measure the relative ultrasonic attenuation coefficient, α , as a function of the applied strain under constant strain rates and cyclic loading conditions. The characteristics of internal damage, measured in terms of α , were determined. Also, a time-dependent cumulative damage model under constant strain rate condition was developed and the applicability of using this model to predict damage was discussed.